

# Concrete, asphalt, rock and masonry saw

## GENERAL DESCRIPTION

This universal saw, completed with the suitable accessory, can be used to cut concrete, asphalt and rock cores, and irregular rock samples in order to obtain geometrically defined samples. It can be fit with 300 to 450 mm dia. blades. The head is adjustable in height. The tilting motor head permit cuts up to 45° inclination. The tank and the trolley are zinc plated to avoid corrosion. Complete with water pump for cooling the blade and double filtering system. Cutting blade, and accessories to cut cores, asphalt, rock and other buiding materials, not included. See accessories.

## TECHNICAL SPECIFICATIONS

- Max. cutting height: 115 mm with 350 mm dia. blade and 165 mm with 450 mm dia. blade
- Max. blade diameter: 450 mm
- Power: 3 kW
- Overall dimensions (lxdxh): 1300x700x700 mm
- Weight approx.: 92 kg

## ORDERING INFO

**55-C0210/D** Concrete, asphalt, rock and masonry saw. 380V, 50 Hz, 3 ph

## ACCESSORIES

- 45-C0211/4** Diamond blade, 350 mm dia., for hard rock
- 45-C0211/5** Diamond blade, 450 mm dia., for hard rock
- 55-C0211/1** Diamond blade, 350 mm dia., for concrete
- 55-C0210/1** Diamond blade, 450 mm dia., for concrete
- 55-C0210/2** Diamond blade, 450 mm dia., for asphalt
- 55-C0210/5** V shaped support for cylinders and cores up to 160 mm dia.  
Weight approx.: 4 kg
- 45-C0210/6** Locking clamp device for irregular pieces.

## DATA SHEET



55-C0210/B fit with 45-C0211/4 diamond blade and  
45-C0210/6 device for irregular pieces



55-C0210/D with 50-C0210/1 diamond blade and  
50-C0210/5 V shaped support.