

Sample Grading

76

Marshall Compactor



Single Automatic Standard-duty 4" indexing compactor

Cat. No. 76-B4446.GIL

Features:

- Automatic system for compacting Marshall samples in stationary 4in moulds
- Automated counter controls number of blows and stops at completion
- Compaction rate of either 55 or 64 blows per minute

Marshall Compactor, Automatic, 4in Mould compacts asphalt samples in a stationary 4in (102mm) mould with an automatic counter controlling the specified number of blows per minute. Operation stops at completion. The unit includes an ASTM-compliant oak pedestal with steel plate, a 10lb (4.5kg), flat-face hammer, and an MSA-100 Stationary Marshall Compaction Mould Set which includes 4in mould, base and collar.

MS-1 models meet ASTM D6926 with 64 blows per minute.

MS-1B models operate at 55 blows per minute.

Included Items:

- Marshall Compactor, Automatic, 4in Mold with 64 or 55 blows/min (115V/60Hz or 230V/50Hz)
- ASTM-compliant Oak Pedestal with steel plate
- 10lb (4.5kg) flat-face hammer
- 4in Stationary Marshall Compaction Mold Set
- Conforms to AASHTO T 245, ASTM D6926, AASHTO R 68, PTM 705



53 Granite Street, GEEBUNG, QLD, 4034, Australia | P.O. Box 124, VIRGINIA, QLD 4014, Australia

Ph.: +61 (0)7 3265 4952 | Fax: +61 (0)7 3265 2713 | Email: sales@geo-con.com.au | Web: www.geo-con.com.au