

# CENTER 300 Series THERMOMETER



- \* Auto Power Off
- \* Resolution 0.1° C , 0.1° F
- \* Simultaneous MAX AVG MIN Measurement
- \* HOLD REL Function
- \* Timer Function (300 302 )
- \* Dual Display( 301 303)
- \* TYPE-K,J Thermocouple Input( 302 303)

CENTER

300 301 TYPE K THERMOMETER



Timer Function



Dual Input/Dual Display

### ● Features

- \* 4 digit LCD
- \* Auto Power Off
- \* MAX,AVG,MIN, Function
- \* HOLD Function
- \* REL Function
- \* Low Battery Indication
- \* Resolution 0.1°C, 0.1°F
- \* External Battery Access Door For Easy Battery Changing

### ● Measurement Range

- \* -200°C ~ 1370°C
- \* -328°F ~ 2498°F

### ● Accuracy

- \* -200°C ~ 1370°C ..... ± 0.3% rdg + 1°C
- \* -328°F ~ 2498°F ..... ± 0.3% rdg + 2°F

### ● Operation Condition

- 0°C ~ 50°C ( 32°F ~ 122°F )
- 0% ~ 80% R.H ( 0°C ~ 35°C, 32°F ~ 95°F )
- 0% ~ 60% R.H ( 35°C ~ 50°C, 95°F ~ 122°F )

### ● Storage Temperature

- 20°C ~ 60°C

### ● Input Protection

- 60V DC or 24Vrms AC Maximum

### ● Battery

- 9V, NEDA 1604, IEC 6F22, JIS 006P

### ● Dimension

- 184mm×64mm×30mm( 7.25"×2.5"×1.2" )

### Weight

- Approx. 210g